



LED A14 Bulb, Dimmable, Frosted, 3W

Replaces Incandescents up to 25 Watts – Omnidirectional – 120VAC – E26 Base



FEATURES

- 2 Year LEDtronics Limited Warranty
- Direct Retrofit into E26 Edison Base Fixtures
- Lumen Maintenance over 70% @ 50,000+ Hours
- Energy Savings of up to 90%
- Omnidirectional Beam Pattern / High CRI
- Dimmable with Standard Lamp Dimmers

APPLICATIONS

- For Indoor/Outdoor Use
- Architectural / Décor Lighting
- Marquee & Sign Lights
- Store Front Displays & Retail Display Cases
- Accent Lighting

Over 30 Years of LEDtronics Design, Engineering & Manufacturing Experience

**E26 BASE
FROSTED**



Replaces Incandescent Bulbs
up to 25 Watts

DEC-A14F-3W-XHW-120AWD

Input Power	2.5 Watts
Input Voltage	120VAC
Input Current	0.030A
Total Lumens	220 lm
Max. Candela	20 cd
Power Factor	0.75
Efficacy	85 lm/W
CRI	>80
Color	Halogen White
Color Temperature	2400K~2700K
Illumination Angle	Omnidirectional
Oper. Temperature	-4°F ~+113°F (-20°C ~+45°C)
Heatsink	Aluminum / Silver
Lens	Tempered Glass / Frosted
Dimensions	3.52 x Ø1.77 inch / 90 x Ø45 mm
Net Weight	0.125 lb / 2.0 oz / 56.7 g



LEDTRONICS®

Creating the Future of LED Light Since 1983™



© 2015 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505

Phone: (800) 579.4875 / (310) 534.1505

Fax: (310) 534.1424

E-mail: info@ledtronics.com

Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative
from our worldwide network:

LEDTRONICS.COM

WWW.LEDTRONICS.COM

LOG 498 / Rev 08-2015

Check LEDTRONICS.COM for latest data.
Printed material may be outdated.

LED A14 Bulb, Dimmable, Frosted, 3 Watts

PHOTOMETRIC REPORT:

DEC-A14F-3W-XHW-120AWD

Filename: DEC-A14F-3W-XHW-120AWD

Manufacturer: LEDTRONICS
Luminaire: FROSTED LENS, DIM, 120VAC, 2.7W
Luminaire Cat: DEC-A14F-3W-XHW-120AWD
Lamp: . LUMEN RATING: 221.1 Lms.
Lamp Output: 1 lamp(s), rated Lumens/lamp: 221.1
Max Candela: 22.6 at Horizontal: 45°, Vertical: 60°
Luminous Opening: Point
Test: 4-23-14
Photometry : Type C
CIE Class: General Diffuse
Cutoff Class: Noncutoff

Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	14.5	6.6%	6.6%
0-40	26.6	12%	12%
0-60	62.4	28.2%	28.2%
60-90	68.3	30.9%	30.9%
70-100	68.3	30.9%	30.9%
90-120	59.0	26.7%	26.7%
0-90	130.8	59.1%	59.1%
90-180	90.3	40.9%	40.9%
0-180	221.1	100%	100%

