



LED A19 Bulb, Frosted, 7 Watts

Replaces Incandescents 60 to 75 Watts – 100~277VAC – 5000K – E26 Base



FEATURES

- 3 Year LEDtronics Warranty
- Direct Retrofit into E26 Edison Base Fixtures
- Directional Candela Exceeds 75 Watt Incandescent
- Lumen Maintenance over 70% @ 50,000+ Hours
- Energy Savings of up to 80%
- High CRI / High Lumen with Wide Light Distribution
- UV-Protected Polycarbonate Diffused Lens
- Solid State: High Shock & High Vibration Resistance
- RoHS Compliant

APPLICATIONS

- Suitable for Damp Locations
- Architectural / Décor Lighting
- Task Lights
- Store Front Displays & Retail Display Cases
- Exhibit Set-ups
- Accent Lighting
- Ceiling Down Lights

Over 30 Years of LEDtronics Design, Engineering & Manufacturing Experience

FROSTED

Replaces Incandescent
Bulbs up to 75 Watts



E26 BASE

DEC-A19F-7W-XPW-001AW

Input Power	7.0 Watts
Input Voltage	100~277VAC
Input Current	0.06A
Total Lumens	745 lm
Max. Candela	170 cd
Power Factor	0.99
Efficacy	105 lm/W
CRI	>80
Color	Pure White
Color Temperature	4500K~5500K
Angle of Illumination	135°
Oper. Temperature	-13°F ~ +104°F / -25°C ~ +40°C
Protection Rating	IP50 – Dust Protected
Heatsink	Aluminum Alloy / Silver
Lens	Polycarbonate / Frosted White
Dimensions	4.65 x 0.236 inch / 118 x 060 mm
Net Weight	6.4 oz / 181.4 g



LEDTRONICS®

America's Premium Brand LED Company™



© 2017 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424
E-mail: info@ledtronics.com
Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:
LEDtronics.com

WWW.LEDTRONICS.COM

LOG 503 / Rev 02-2017

Check LEDTRONICS.COM for latest data.
Printed material may be outdated.

Luminaire Photometric Report

Filename: DEC-A19F-7W-XPW-001AW

Manufacturer: LEDTRONICS -

Luminaire: FROSTED LENS, 120VAC, 7.0W

Luminaire Cat: DEC-A19F-7W-XPW-001AW

Lamp: LUMEN RATING: 747.4Lms.

Lamp Output: 1 lamp(s), rated Lumens/lamp: 747.7

Max Candela: 169.0 at Horizontal: 0°, Vertical: 0°

Luminous Opening: Point

Test: 12-19-13

Photometry : Type C

CIE Class: Semi-Direct

Cutoff Class: Noncutoff

Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	135.0	18.1%	18.1%
0-40	226.4	30.3%	30.3%
0-60	427.2	57.1%	57.1%
60-90	218.0	29.2%	29.2%
70-100	166.8	22.3%	22.3%
90-120	81.4	10.9%	10.9%
0-90	645.2	86.3%	86.3%
90-180	102.5	13.7%	13.7%
0-180	747.7	100%	100%

Illuminance at a Distance

	Center Beam FC	Beam Width
1.7ft	60.84 fc	8.2ft
3.3ft	15.21 fc	16.3ft
5.0ft	6.76 fc	24.5ft
6.7ft	3.80 fc	32.6ft
8.3ft	2.43 fc	40.8ft
10.0ft	1.69 fc	48.9ft

■ Beam Spread: 135.5°

