



LED Outdoor Area Flood Light / 40W

Replaces HID Lamps up to 150W – Suitable for Wet Locations – Full Cutoff 120° Beam



FEATURES

- 5 Year LEDtronics Warranty
- Energy Savings of up to 75%
- Wide Voltage Range: 100~277VAC
- IP65 Protection for Wet Locations
- Full Cutoff / Reduced Light Pollution
- Lumen Maintenance over 70% @ 50,000+ Hours
- Solid-State: High Shock & High Vibration Resistant
- Rugged, Die-Cast Aluminum Housing
- UL/cUL Listed (JLS68103-G40FC-WPCL)
- RoHS Compliant
- Photocell, 3 ft. Power Cord
- LM79 Report Available

APPLICATIONS

- Building Entrance Lighting
- Perimeter Security Lighting / Parking Areas
- Warehouses, Loading Platforms
- Signage Illumination
- Walkways, Underpasses
- Recreation Areas


More than 30 Years of LEDtronics Design, Engineering & Manufacturing Experience



5000K Pure White

WWL15-20X2W-XPW-101W

Input Power	40 Watts
Input Voltage	100~277VAC (Tested @ 120VAC)
Total Lumens	3150 lm
Max. Candela	1235 cd
Power Factor	1.0
Efficacy	80 lm/W
Viewing Angle	120° / Full Cutoff
Emitted Color	Pure White
Color Temperature	5000K~5600K
CRI	>70
Oper. Temperature	-30°C ~ +60°C -22°F ~ +140°F
Protection Rating	IP65
Housing	Die-Cast Aluminum / Arch. Bronze
Lens	Tempered Glass / Clear
Dimensions	W13.05 x H11.46 x D9.05 inch W331 X H291 X D230 mm
Net Weight	5.7 lbs / 2.585 kg



LEDTRONICS®

Creating the Future of LED Light Since 1983™



© 2014 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
 Phone: (800) 579.4875 / (310) 534.1505
 Fax: (310) 534.1424
 E-mail: info@ledtronics.com
 Website: ledtronics.com



To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDTRONICS.COM

WWW.LEDTRONICS.COM

LOG 540 / Rev 09-2014

Check LEDTRONICS.COM for latest data. Printed material may be outdated.

LED Outdoor Full Cutoff Wall Pack / 40 Watts

PHOTOMETRIC REPORT: WWL15-20X2W-XPW-101W

Filename: WWL15-20X2W-XPW-101W

Luminaire: 120VAC, 350mA, 42.0W, 1.0PF
 Lamp: LED
 Lamp Cat: LUMINAIRE OUTPUT = 3148LMS
 Lamp Output: 1 lamp(s), rated Lumens/lamp: 3148
 Max Candela: 1,237.0 at Horizontal: 0°, Vertical: 5°
 Luminous Opening: Point
 Test: 7/31/2014
 Test Lab: LEDTRONICS
 Photometry : Type C
 CIE Class: Direct
 Cutoff Class: Full Cutoff
 Nema Type: 7 X 7

Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	115.2	3.7%	90-100	0	0%
10-20	324.4	10.3%	100-110	0	0%
20-30	480.5	15.3%	110-120	0	0%
30-40	564.5	17.9%	120-130	0	0%
40-50	572.1	18.2%	130-140	0	0%
50-60	507.8	16.1%	140-150	0	0%
60-70	376.2	12.0%	150-160	0	0%
70-80	184.2	5.9%	160-170	0	0%
80-90	23.2	0.7%	170-180	0	0%

