



LED T8 Ballast-Ready/Dual Mode Tube Lights

2 ft – 10 Watts – Clear or Frosted Lens – 100~277VAC – 110° Wide Beam – 2 Pin / G13 Base



FEATURES

- 5 Year LEDtronics Limited Warranty
- Direct Retrofit into 2-ft Fluorescent T8 Fixtures
- Energy Savings of up to 50%
- Lumen Maintenance over 70% @ 50,000+ Hours
- Even Lighting, No Buzzing, No Flickering
- No UV/IR Radiation, No RF Interference
- UL/cUL Listed (E358956, ZY-T8-10W600)
- No Toxic Mercury - RoHS Compliant

APPLICATIONS

- Office Lighting
- Production Area & Warehouse Lighting
- Coolers, Freezers & Damp Locations
- Retail Store Display Lighting
- Parking Garages, Transportation
- Undercabinet Lighting
- General & Street Sign Backlighting



Over 35 Years of LEDtronics Design, Engineering & Manufacturing Experience

FROSTED

- LED24T8BR-10W-XIW-101WF (Warm White)
- LED24T8BR-10W-XWW-101WF (Natural White)
- LED24T8BR-10W-XPW-101WF (Pure White)

	WARM WHITE	NATURAL WHITE	PURE WHITE
Input Power	10 Watts	9.4 Watts	9.5 Watts
Input Voltage	100~277VAC (Tested @120VAC)		
Input Current	0.086A	0.080A	0.081A
Total Lumens	1138 lm	1386 lm	1425 lm
Max. Candela	292 cd	349 cd	348 cd
Power Factor	0.97	0.97	0.97
Efficacy	114 lm/W	148 lm/W	150 lm/W
CRI	>80	>80	>80
Color Temp.	3000K	4000K	5000K
Illum. Angle	105° x 145°	105° x 150°	110° x 145°
Oper. Temp.	-22°F to 104°F (-30°C to 40°C)		
Heatsink	Aluminum / Silver Color		
Lens	Polycarbonate / Frosted White		
Base	2-Pin G13		
Dimensions	23.8 x Ø1.2 inch / 604 x Ø30 mm		
Net Weight	0.36 lbs / 160 g		

2 Ft FROSTED


Uses 10 Watts, Replaces Fluorescents up to 16W

2 Ft CLEAR

CLEAR

- LED24T8BR-10W-XWW-101WC (Natural White)
- LED24T8BR-10W-XPW-101WC (Pure White)

	NATURAL WHITE	PURE WHITE
Input Power	9 Watts	
Input Voltage	100~277VAC (Tested @120VAC)	
Input Current	0.080A	
Total Lumens	1100 lm	1050 lm
Max. Candela	410 cd	276 cd
Power Factor	0.9	
Efficacy	115 lm/W	117 lm/W
CRI	83	
Color Temperature	4000K	5000K
Illumination Angle	110° x 110°	
Oper. Temperature	-22°F to 104°F (-30°C to 40°C)	
Heatsink	Aluminum / Silver Color	
Lens	Polycarbonate / Clear	
Base	2-Pin G13	
Dimensions	23.78 x Ø1.0 inch / 1213 x Ø25.4 mm	
Net Weight	0.4 lbs / 6.4 oz / 181.4 g	



Works with Any T8 Fluorescent Electronic Ballast – No Ballast Bypass Required
Alternatively, Directly Installs into Ballast-Free Tube Light Fixtures

LEDTRONICS®

America's Premium Brand LED Company™



© 2022 LEDtronics, Inc.



23105 Kashiwa Court, Torrance, CA 90505
 Phone: (800) 579.4875 / (310) 534.1505
 Fax: (310) 534.1424
 E-mail: info@ledtronics.com
 Website: ledtronics.com

To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDTRONICS.COM

WWW.LEDTRONICS.COM

L06 597 / Rev 05-2022

Check LEDTRONICS.COM for latest data. Printed material may be outdated.