



# LED T8 Composite Tube Lights, 2 ft

10 Watts – 4000K or 5000K – Clear or Frosted Lens – 100~277VAC – 2 Pin / G13 Base – ETL



## FEATURES

- 5 Year LEDtronics Limited Warranty
- Direct Retrofit into 2 Ft Fluorescent T8/T12 Fixtures
- Energy Savings of up to 50%
- Lumen Maintenance over 70% @ 50,000+ Hours
- Even Lighting, No Buzzing, No Flickering
- No UV/IR Radiation, No RF Interference
- ETL Classified (5014001)
- No Toxic Mercury
- LM79 & LM80 Reports Available



## APPLICATIONS

- Office Lighting
- Production Area
- Warehouse Lighting
- Coolers, Freezers & Damp Locations
- Retail Store Display Lighting
- Transportation
- Undercabinet Lighting
- General & Street Sign Backlighting

## AVAILABLE OPTIONS

- Other Tube Lengths
- Other Color Temperatures
- Other Voltages

40 Years of LEDtronics Design,  
Engineering & Manufacturing Experience

### Frosted Lens

LED24T8CM-10W-XWW-101WF (Natural White)  
LED24T8CM-10W-XPW-101WF (Pure White)

	XWW	XPW
Input Power	9.81 Watts	10 Watts
Input Voltage	100~277VAC (Tested @ 120VAC)	
Input Current	0.085A	0.085A
Total Lumens	1175.1 lm	1200 lm
Max. Candela	255 cd	270 cd
Power Factor	0.876	0.9
Efficacy	119.79 lm/W	120 lm/W
CRI	83	80
Color Temperature	3800K~4300K	5000K~5600K
Illumination Angle	105° x 160°	
Dimmability	Not Dimmable	
Oper. Temperature	-4°F to 113°F (-20°C to 45°C)	
Heatsink	Aluminum Alloy / Silver Color	
Lens	Polycarbonate / Frosted White	
Base	2-Pin G13	
Dimensions	23.78 x Ø1.02 inch / 604 x Ø26 mm	
Net Weight	0.325 lbs / 147.4 g	
DLC Product Code	PL6TIZDPRJ8	PLHLPCZ8YVLX

2 Ft  
FROSTED

Uses 10 Watts,  
Replaces Fluorescents up to 16W

2 Ft  
CLEAR

### Clear Lens

LED24T8CM-10W-XWW-101WC (Natural White)  
LED24T8CM-10W-XPW-101WC (Pure White)

	XWW	XPW
Input Power	10 Watts	
Input Voltage	100~277VAC (Tested @ 120VAC)	
Input Current	0.085A	0.090A
Total Lumens	1200 lm	
Max. Candela	420 cd	
Power Factor	0.9	
Efficacy	120 lm/W	
CRI	80	80
Color Temperature	3800K~4300K	5000K~5600K
Illumination Angle	115° x 125°	110° x 125°
Dimmability	Not Dimmable	
Oper. Temperature	-4°F to 113°F (-20°C to 45°C)	
Heatsink	Aluminum Alloy / Silver Color	
Lens	Polycarbonate / Clear	
Base	2-Pin G13	
Dimensions	23.78 x Ø1.02 inch / 604 x Ø26 mm	
Net Weight	0.325 lbs / 147.4 g	
DLC Product Code	PLG8HMVQK9HH	PLSUB340EBVV



# LEDTRONICS®

America's Premium Brand LED Company™



© 2023 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505  
 Phone: (800) 579.4875 / (310) 534.1505  
 Fax: (310) 534.1424  
 E-mail: info@ledtronics.com  
 Website: ledtronics.com



To order LEDtronics products,  
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:  
**LEDtronics.com**

WWW.LEDTRONICS.COM

LOG 599 / Rev 12-2023

Check LEDTRONICS.COM for latest data.  
Printed material may be outdated.