



LED Filament-Look Dimmable Globe Bulbs

2 to 5 Watts – 120VAC – 2700K to 5000K White – E12 or E26 Base – Clear or Frosted Lens



WWW.LEDTRONICS.COM

LOG 624 / Rev 07-2020

Check LEDTRONICS.COM for latest data.
Printed material may be outdated.



All lamps feature phosphor LED filaments evenly spaced on a sapphire bracket that is attached to a precision-guided lamp post in a vacuum-sealed and insulated environment

FEATURES

- 3 Year LEDtronics Warranty
- Directly Replaces Incandescent, Halogen & CFL Bulbs in E12 (02WE12C) or E26 Base Fixtures
- Lumen Maintenance over 70% @ 25,000+ Hours
- Energy Savings of up to 85%
- Dimmable Only with Low-Wattage LED Dimmers (such as Lutron DVCL-153P Diva)
- High Lumen, High CRI, Low Glare
- No UV/IR, No RF Interference
- High-Shock, Impact & Vibration Resistant
- UL/cUL Listed: E476884
- Eco-Friendly – RoHS Compliant

APPLICATIONS

- Architectural Lighting
- Task Lights
- Accent Lighting

AVAILABLE OPTIONS

- Other Color Temperatures
- Other Wattages
- Other Base Sizes

Over 35 Years of LEDtronics Design, Engineering & Manufacturing Experience

CLEAR LENS

FILG11-02WE12C-XHW-101*
FILG11-02WE12C-XPW-101
FILG25-06WE26C-XHW-101
FILG30-06WE26C-XHW-101
FILG40-06WE26C-XHW-101



	FILG11-XHW	FILG11-XPW	FILG25	FILG30	FILG40
Input Power	2 Watts	2.5 Watts	5 Watts	5 Watts	5 Watts
Input Voltage	120VAC				
Input Current	0.016A	0.022A	0.050A	0.050A	0.050A
Total Lumens	184 lm	247 lm	585 lm	545 lm	575 lm
Efficacy	115 lm/W	99 lm/W	115 lm/W	110 lm/W	115 lm/W
Power Factor	0.80				
Color	Halogen White	Pure White	Halogen White	Halogen White	Halogen White
CCT	2700K	5000K	2700K	2700K	2700K
CRI	82	>80	>80	>80	>80
Beam Angle	Omnidirectional				
Lens	Clear Glass				
LED Filaments	2	4	6	6	6
Base	E12 Candelabra Screw		E26 Medium Screw	E26 Medium Screw	E26 Medium Screw
Operating Temp.	-40°F ~ 122°F / -40°C ~ 50°C				
Protection Rating	IP20 – Protected against Solid Objects over 12mm				
Dimensions (typ.)	2.42" x 0.135" inch / 61 x 034 mm		4.72" x 0.315" inch / 120 x 080 mm	5.36" x 0.376" inch / 136 x 095 mm	6.9" x 0.492" inch / 175 x 0125 mm
Net Weight	0.4 oz / 11.34 g		1.6 oz / 45.36 g	1.8 oz / 51.03 g	3.2 oz / 90.72 g

* Title 20 Compliant

LEDTRONICS®

America's Premium Brand LED Company™



© 2020 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505

Fax: (310) 534.1424

E-mail: info@ledtronics.com

Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDTRONICS.COM

LED Dimmable Filament-Look Bulb: G25, G30, G40 – Frosted

2

FILG25-06WE26F-XHW-101
FILG30-06WE26F-XHW-101
FILG40-06WE26F-XHW-101
FILG40-06WE26F-XIW-101

FROSTED LENS

	FILG25	FILG30	FILG40-XHW	FILG40-XIW
Input Power	5 Watts	5 Watts	4.5 Watts	5 Watts
Input Voltage	120VAC			
Input Current	0.050A	0.050A	0.045A	0.046A
Total Lumens	545 lm	570 lm	530 lm	520 lm
Efficacy	105 lm/W	115 lm/W	115 lm/W	100 lm/W
Max. Candela	55 cd	-	-	54 cd
Power Factor	0.85	0.80	0.80	0.80
Color	Halogen White			Warm White
CCT	2700K			3000K
CRI	>80			
Beam Angle	Omnidirectional			
Lens	Glass, Frosted White			
LED Filaments	6			
Base	E26 Medium Screw			
Operating Temp.	-40°F ~122°F / -40°C ~50°C			
Protection Rating	IP20 – Protected against Solid Objects over 12mm			
Dimensions	4.72" x 3.15" inch 120 x 80 mm	5.33" x 0.69" inch 135 x 0.93 mm	6.77" x 0.92" inch 172 x 0.125 mm	6.80" x 0.92" inch 173 x 0.125 mm
Net Weight	1.6 oz / 45.36 g	1.8 oz / 51.03 g	3.2 oz / 90.72 g	3.4 oz / 96.39 g



LED Dimmable Filament-Look Bulbs: G14/G15 – Clear or Frosted

FILG15-02WE26C-XHW-101
FILG15-04WE26C-XHW-101

CLEAR LENS

FILG15-02WE26F-XHW-101
FILG15-04WE26F-XHW-101

FROSTED LENS

	2WE26C	4WE26C	2WE26F	4WE26F
Input Power	1.5~2 Watts	4 Watts	2 Watts	4 Watts
Input Voltage	120VAC			
Input Current	0.016A	0.034A	0.016A	0.034A
Total Lumens	130 lm	434 lm	202 lm	429 lm
Efficacy	87 lm/W	124 lm/W	126 lm/W	122 lm/W
Power Factor	0.80			
Color	Halogen White			
CCT	2700K			
CRI	>80			
Beam Angle	Omnidirectional			
Lens	Clear Glass		Glass, Frosted White	
LED Filaments	2	4	2	4
Base	E26 Medium Screw			
Operating Temp.	-40°F ~122°F / -40°C ~50°C			
Protection Rating	IP20 – Protected against Solid Objects over 12mm			
Dimensions	2.83" x 0.174" inch / 72 x 0.44 mm			
Net Weight	0.8 oz / 22.7 g			



OTHER AVAILABLE
FILAMENT-LOOK
LED LAMPS

