



LED Compact Outdoor Wall-Pack Floodlights

25 Watts – 120~277VAC – Extended Fresnel Lens – 40° x 95° Beam – 3000K & 5000K White



FEATURES

- 5 Year LEDtronics Warranty
- Energy Savings of up to 75%
- Wide Voltage Range: 120~277VAC
- ETL/cETL Listed: 4007109 (WP01B-25)
- Even Lighting: High Intensity, Reduced Light Pollution
- Lumen Maintenance over 75% @ 50,000+ Hours
- Solid-State: High Shock & High Vibration Resistant
- Rugged, Die-cast, Aluminum-Alloy Bronze Housing
- External LED Driver, Funnel Heatsink, Fresnel Lens
- RoHS Compliant – No Toxic Metals (XPW)
- Highest-Grade White LEDs

APPLICATIONS

- Ideal for Mounting Heights below 15 Feet
- Exterior Wall & Area Lighting
- Perimeter Security Lighting
- Recreational & Parking Areas
- Walkways, Stairwells, Corridors, Alcoves, Underpasses & Corners
- Building Entrance Lighting
- Loading Platforms/Warehouses
- Signage Illumination
- Ideal for Use with Alternate or Renewable Energy Resources – Solar & Wind Power

WWW.LEDTRONICS.COM

LOG 642 / Rev 07-2022

Check LEDTRONICS.COM for latest data. Printed material may be outdated.



AVAILABLE OPTIONS

- Other Wattages & Higher Voltages
- Other White Color Temperatures
- Photo Sensors / Dimming

40 Years of LEDtronics
Design, Engineering & Manufacturing Experience

Suggested Replacement:
up to 100W MH/HPS



Extended Lens /
Forward Throw

WWL12-25W-XIW-101 (Warm White)

WWL12-25W-XPW-101 (Pure White)

	XIW	XPW
Emitted Color	Warm White	Pure White
Color Temperature	3000K	5000K
Input Power	23.1 Watts	24.3 Watts
Input Voltage	120~277VAC (Tested @ 120VAC)	
Input Current	0.190A	0.203A
Total Lumens	1138.8 lm	1172 lm
Efficacy	49 lm/W	48 lm/W
Max. Candela	852 cd	840 cd
Power Factor	≥0.90	0.99
Viewing Angle	35° x 95°	40° x 95°
CRI	≥80	
Dimmability	Not Dimmable	
Oper. Temperature	-40°C ~ +40°C / -40°F ~ +104°F	
Housing	Aluminum Alloy / Bronze Color	
Lens	Clear Glass / Fresnel	
Dimensions	W14.37 x H7.66 x D9.22 inch / W365 x H194 x D234 mm	
Net Weight	7.33 lbs / 3.33 kg	



LEDTRONICS

America's Premium Brand LED Company™



© 2022 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
 Phone: (800) 579.4875 / (310) 534.1505
 Fax: (310) 534.1424
 E-mail: info@ledtronics.com
 Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative
from our worldwide network:

LEDtronics.com