



LED Filament-Look Dimmable A19 Bulbs

2 to 7 Watts – 120VAC – 2200K to 4000K – Omnidirectional Beam – E26 Base – Clear or Frosted Lens



All lamps feature phosphor LED filaments evenly spaced on a sapphire bracket that is attached to a precision-guided lamp post in a vacuum-sealed and insulated environment

FEATURES

- 3 Year LEDtronics Warranty
- Directly Replaces Incandescent, Halogen & CFL Bulbs in E26 Base Fixtures
- Lumen Maintenance over 70% @ 25,000+ Hours
- Energy Savings of up to 85%
- Dimmable Only with Low-Wattage LED Dimmers (such as Lutron DVCL-153P Diva)
- High Lumen, High CRI, Low Glare
- No UV/IR, No RF Interference
- High-Shock, Impact & Vibration Resistant
- UL/cUL Listed: E476884
- Eco-Friendly – RoHS Compliant

APPLICATIONS

- Architectural Lighting
- Task & Reading Lights, Table Lamps
- Accent & Vanity Mirror Lights

AVAILABLE OPTIONS

- Other Color Temperatures
- Other Voltage: 240VAC
- Amber-Tinted or Milky-White Lens
- Other Bases: E27, B22

Over 35 Years of LEDtronics Design, Engineering & Manufacturing Experience

CLEAR LENS

- FILA19-02WE26C-XHW-101
- FILA19-04WE26C-XFW-101
- FILA19-04WE26C-XHW-101
- FILA19-06WE26C-XHW-101
- FILA19-08WE26C-XHW-101
- FILA19-10WE26C-XHW-101



	2WE26C-XHW	4WE26C-XFW	4WE26C-XHW	6WE26C-XHW	8WE26C-XHW	10WE26C-XHW
Input Power	2 Watts	3 Watts	4 Watts	5 Watts	7 Watts	7 Watts
Input Voltage	120VAC					
Input Current	0.016A	0.028A	0.035A	0.050A	0.064A	0.066A
Total Lumens	193 lm	218 lm	280 lm	445 lm	506 lm	704 lm
Efficacy	107 lm/W	66 lm/W	78 lm/W	87 lm/W	78 lm/W	102 lm/W
Max. Candela	22 cd	26 cd	36 cd	53 cd	55 cd	75 cd
Power Factor	0.80	0.80	0.80	0.80	0.86	0.86
Color	Halogen White	Filament White	Halogen White	Halogen White	Halogen White	Halogen White
CCT	2700K	2200K	2700K	2700K	2700K	2700K
CRI	83	>80	>80	>80	>80	>80
Beam Angle	Omnidirectional					
Lens	Clear Glass					
LED Filaments	2	4	4	6	8	10
Base	E26 Medium Screw					
Operating Temp.	-40°F ~ 122°F / -40°C ~ 50°C					
Protection Rating	IP50 – Dust Protected					
Dimensions (typ.)	4.08" x 0.236" inch / 104 x 060 mm					
Net Weight	0.8 oz / 22.7 g					

LEDTRONICS®

America's Premium Brand LED Company™



© 2018 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424

E-mail: info@ledtronics.com
Website: ledtronics.com



To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:
LEDTRONICS.COM

WWW.LEDTRONICS.COM

LOG 653 / Rev 07-2020

Check LEDTRONICS.COM for latest data. Printed material may be outdated.

FROSTED LENS

- FILA19-02WE26F-XHW-101
- FILA19-04WE26F-XHW-101
- FILA19-06WE26F-XHW-101
- FILA19-06WE26F-XIW-101
- FILA19-06WE26F-XNW-101
- FILA19-08WE26F-XHW-101*
- FILA19-08WE26F-XIW-101
- FILA19-08WE26F-XNW-101
- FILA19-10WE26F-XHW-101



	2WE26F-XHW	4WE26F-XHW	6WE26F-XHW	6WE26F-XIW	6WE26F-XNW	8WE26F-XHW	8WE26F-XIW	8WE26F-XNW	10WE26F-XHW
Input Power	2 Watts	4 Watts	5 Watts	5 Watts	5 Watts	6 Watts	7 Watts	7 Watts	7 Watts
Input Voltage	120VAC								
Input Current	0.016A	0.035A	0.052A	0.050A	0.050A	0.062A	0.064A	0.063A	0.065A
Total Lumens	188 lm	356 lm	471 lm	468 lm	453 lm	561 lm	577 lm	636 lm	713 lm
Efficacy	105 lm/W	99 lm/W	87 lm/W	90 lm/W	89 lm/W	88 lm/W	87 lm/W	98 lm/W	108 lm/W
Max. Candela	20 cd	37 cd	48 cd	49 cd	46 cd	56 cd	57 cd	61 cd	70 cd
Power Factor	0.80	0.80	0.80	0.85	0.85	0.80	0.86	0.86	0.86
Color	Halogen White	Halogen White	Halogen White	Warm White	Natural White	Halogen White	Warm White	Natural White	Halogen White
CCT	2700K	2700K	2700K	3000K	4000K	2700K	3000K	4000K	2700K
CRI	>80								
Beam Angle	Omnidirectional								
Lens	Glass, Frosted White								
LED Filaments	2	4	6	6	6	8	8	8	10
Base	E26 Medium Screw								
Operating Temp.	-40°F ~122°F / -40°C ~50°C								
Protection Rating	IP50 – Dust Protected								
Dimensions (typ.)	4.08" x 02.36" inch / 104 x 060 mm								
Net Weight	0.8 oz / 22.7 g								

All lamps feature phosphor LED filaments evenly spaced on a sapphire bracket that is attached to a precision-guided lamp post in a vacuum-sealed and insulated environment

* Title 20 Compliant

OTHER AVAILABLE FILAMENT-STYLE LED LAMPS

