



LED Extended Lens Wall Pack Floodlights

60, 80 & 120 Watts – 100 to 277VAC – 5000K White – 115° Beam – IP65 – UL Listed



FEATURES

- 5 Year LEDtronics Warranty
- Lumen Maintenance over 70% @ 50,000+ Hours
- Durable Die-cast Aluminum Housing
- UL/cUL (E330342) Listed
- Energy Savings of up to 75%
- Indoor/Outdoor Use: Suitable for Wet Locations
- High Lumen & Efficacy / 115° Wide Beam
- Solid-State: High-Shock & Vibration Resistant
- No UV/IR Radiation, Eco-Friendly – RoHS Compliant

APPLICATIONS

- Perimeter Security Lighting
- Building Entrance Lighting
- Warehouses, Loading Platforms
- Landscape Lighting
- Walkways, Underpasses & Pathways
- Recreation Areas
- Architectural Wall Washing
- Signs & Billboards
- Parking Lot Lighting
- Emergency Exit Way Lighting



Over 35 Years of LEDtronics Design,
Engineering & Manufacturing Experience

AVAILABLE OPTIONS

- 4000K, 4500K & 5700 White CCT Colors
- Other Wattages: 100W
- "Made in USA" ARRA Compliance

60 Watts, Replaces
MH Lamps up to 150W

WLPE14-060W-XPW-105

Input Power	60.7 Watts
Input Voltage	100~277VAC (Tested @ 120VAC)
Input Current	0.502A
Power Factor	0.91
Total Lumens	7052 lm
Efficacy	116 lm/W
Max. Candela	2,596 cd
CRI	83
Illumination Angle	115°
Emitted Color	Pure White
Color Temperature	5000K
Dimmability	Not Dimmable
Oper. Temperature	-4°F ~+113°F / -20°C ~+45°C
Oper. Humidity	20% - 90% RH
Housing	ADC12 Aluminum / Brown Finish
Lens Material	Clear, Polycarbonate
Protection Rating	IP65
Dimensions (L x W x H)	14.24 x 9.98 x 9.28 inch 361.7 x 253.5 x 235.7 mm
Weight	7.87 lbs / 3.57 kg



LM79 Reports on File



80 Watts, Replaces
MH Lamps 175~200W

WLPE14-080W-XPW-105

Input Power	79.8 Watts
Input Voltage	100~277VAC (Tested @ 120VAC)
Input Current	0.687A
Power Factor	0.94
Total Lumens	9885 lm
Efficacy	124 lm/W
Max. Candela	3,224 cd
CRI	83
Illumination Angle	115°
Emitted Color	Pure White
Color Temperature	5000K
Dimmability	Not Dimmable
Oper. Temperature	-4°F ~+113°F / -20°C ~+45°C
Oper. Humidity	20% - 90% RH
Housing	ADC12 Aluminum / Brown Finish
Lens Material	Clear, Polycarbonate
Protection Rating	IP65
Dimensions (L x W x H)	14.24 x 9.98 x 9.28 inch 361.7 x 253.5 x 235.7 mm
Weight	7.87 lbs / 3.57 kg

LEDTRONICS
America's Premium Brand LED Company™



© 2018 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424
E-mail: info@ledtronics.com
Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDTRONICS.COM

LED Extended-Lens Wall Pack Floodlight – 120 Watts



*115-Degree
Wide Beam*



**120 Watts, Replaces
MH Lamps 360~400W**

WLPE18-120W-XPW-105

Input Power	120.6 Watts
Input Voltage	100~277VAC (Tested @ 120VAC)
Input Current	0.968A
Power Factor	0.97
Total Lumens	14,777 lm
Efficacy	122.53 lm/W
Max. Candela	5,048 cd
CRI	83
Illumination Angle	115°
Emitted Color	Pure White
Color Temperature	5000K
Dimmability	Not Dimmable
Oper. Temperature	-4°F ~+113°F / -20°C ~+45°C
Oper. Humidity	20% - 90% RH
Housing	Die-Cast ADC12 Aluminum / Brown Finish
Lens Material	Clear, Polycarbonate
Protection Rating	IP65
Dimensions (L x W x H)	14.24 x 9.98 x 9.28 inch 361.7 x 253.5 x 235.7 mm
Weight	7.87 lbs / 3.57 kg

APPLICATIONS



*LEDtronics LED Wall-Pack
Luminaires Illuminate Outdoor
Areas at Locations around the World*