



# LED A19 Light Bulb: Dimmable, Frosted

8 Watts – 120VAC – 5000K Pure White – 360° Omnidirectional Beam – E26 Base – UL



## FEATURES

- 3 Year LEDtronics Warranty
- Direct Retrofit into E26 Edison Medium Base Fixtures
- Energy Savings of up to 80%
- Long Lifespan: 25,000 Hours
- Operates on 120VAC, Instant On/Off, No Power Surge
- Dimmable with Most TRIAC Dimmers, 10-100% Intensity; Dims 0-100% with Lutron TRIAC Dimmers
- Omnidirectional Beam Pattern, High CRI
- High-Intensity, Even Light Output, No Halation
- No UV or IR Radiation, No RF, No Mercury
- Solid-State: High Shock & Vibration Resistant
- UL/cUL Listed: E469977 (EA19-9W5050cec-2)

## APPLICATIONS

- Architectural & Décor Lighting
- Table Lamps / Task Lights
- Store Front Displays, Retail Display Cases, Signage
- Exhibit Set-ups
- Accent Lighting & Sconces
- Ceiling Down Lights
- Suitable for Damp Locations

40 Years of LEDtronics Design, Engineering & Manufacturing Experience

8 Watts, Replaces Incandescent Lamps up to 60 Watts



## DEC-A19F-10W-XPW-101AD

|                           |                                  |
|---------------------------|----------------------------------|
| <b>Input Power</b>        | 8 Watts                          |
| <b>Input Voltage</b>      | 120VAC                           |
| <b>Input Current</b>      | 0.07A                            |
| <b>Total Lumens</b>       | 1029 lm                          |
| <b>Efficacy</b>           | 129 lm/W                         |
| <b>Max. Candela</b>       | 126 cd                           |
| <b>Power Factor</b>       | 0.95                             |
| <b>Illumination Angle</b> | 360°                             |
| <b>CRI</b>                | >90                              |
| <b>Emitted Color</b>      | Pure White                       |
| <b>Color Temperature</b>  | 5000K                            |
| <b>Heatsink</b>           | Aluminum                         |
| <b>Body</b>               | Polycarbonate / White            |
| <b>Lens</b>               | Polycarbonate / Frosted White    |
| <b>Base Type</b>          | E26 Edison Medium Screw Base     |
| <b>Oper. Temperature</b>  | -4°F ~+104°F / -20°C ~+40°C      |
| <b>Dimmability</b>        | Dimmable 10-100%                 |
| <b>Dimensions</b>         | 4.18 x Ø2.36 inch / 106 x Ø60 mm |
| <b>Net Weight</b>         | 0.09 lbs / 40.82g                |



# LEDTRONICS®

America's Premium Brand LED Company™



23105 Kashiwa Court, Torrance, CA 90505  
Phone: (800) 579.4875 / (310) 534.1505

Fax: (310) 534.1424

E-mail: [info@ledtronics.com](mailto:info@ledtronics.com)

Website: [ledtronics.com](http://ledtronics.com)



© 2023 LEDtronics, Inc.

To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

[LEDtronics.com](http://LEDtronics.com)

WWW.LEDTRONICS.COM

LOG 717 / Rev 05-2023

Check LEDTRONICS.COM for latest data. Printed material may be outdated.

## Luminaire Photometric Report

Filename: DEC-A19F-10W-XPW-101AD

Manufacturer: LEDTRONICS

Luminaire: FROSTED LENS, 9.7W, 120VAC

Lamp Output: 1 lamp, rated Lumens/lamp: 939

Max Candela: 166.0 at Horizontal: 90°, Vertical: 10°

Luminous Opening: Point

Test: 3-19-20

Photometry : Type C

CIE Class: Semi-Direct

Cutoff Class: Noncutoff

### Lumens Per Zone

| Zone  | Lumens | % Total | Zone    | Lumens | % Total |
|-------|--------|---------|---------|--------|---------|
| 0-10  | 15.6   | 1.7%    | 90-100  | 63.7   | 6.8%    |
| 10-20 | 45.9   | 4.9%    | 100-110 | 48.6   | 5.2%    |
| 20-30 | 73.2   | 7.8%    | 110-120 | 35.7   | 3.8%    |
| 30-40 | 94.7   | 10.1%   | 120-130 | 25.1   | 2.7%    |
| 40-50 | 108.0  | 11.5%   | 130-140 | 16.9   | 1.8%    |
| 50-60 | 111.9  | 11.9%   | 140-150 | 10.5   | 1.1%    |
| 60-70 | 107.2  | 11.4%   | 150-160 | 4.6    | 0.5%    |
| 70-80 | 95.8   | 10.2%   | 160-170 | 1.5    | 0.2%    |
| 80-90 | 80.2   | 8.5%    | 170-180 | 0      | 0%      |

