



Compact LED Tube Bulb, Low Voltage

24 or 28 VAC/VDC – Ba15d Base – 130°~160° Beam Angle – 3000K White



FEATURES

- 3 Year LEDtronics Warranty
- Direct Incandescent Replacement
- Low Power Consumption, High Intensity
- Energy Savings up to 90%
- Lumen Maintenance over 70% @ 15,000 Hours
- Compact Bulb Fits in Enclosed Fixtures & Tight Spaces
- Nickel Plated Brass/Dual-Contact Bayonet Base
- Wide Operating Temp. Range: ~-22°F to ~+122°F
- Solid-State: High-Shock & Vibration Resistant
- No UV, No RF Interference, Minimal Heat
- Sunlight-Visible LEDs, Even Lighting

APPLICATIONS

- Suitable for Enclosed Fixtures Where Temperatures Do Not Commonly Exceed the Recommended Operating Range
- Replaces Bayonet-Based Lamps Operating at 24VAC/28VAC ~ 28VAC/28VDC within Its Dimensional Constraints
- Indicator Lights for Instrumentation
- Panel-Mount Pilot Lights
- Accent Lighting

AVAILABLE OPTIONS

- Other Color Temperatures
- Other Voltages

Over 35 Years of LEDtronics Design, Engineering & Manufacturing Experience

Replaces Incandescent Bulbs 72, 624, 5626

3000K Warm White

Replaces Incandescent Bulbs 304, 1252




DB605SM-XIW-024V

Input Voltage	24VAC	24VDC
Input Power	1.3 Watts	1.2 Watts
Input Current	0.054A	0.050A
Efficacy (lm/W)	40	47
Total Lumens	51.7 lm	56.3 lm
Luminous Intensity	4.2 cd	7.1 cd
SCP	4.1	4.5
Power Factor	1.0	
Emitted Color	Warm White	
Color Temp.	3000K	
CRI	75	
Viewing Angle	140°	130°
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x W0.63 inch / L36.58 x W016 mm	
Weight	0.02 lb / 0.3 oz / 8.5 g	

DB605SM-XIW-028V

Input Voltage	28VAC	28VDC
Input Power	1.1 Watts	1.0 Watts
Input Current	0.039A	0.037A
Efficacy (lm/W)	38.18	45
Total Lumens	42 lm	45 lm
Luminous Intensity	1.6 cd	4.8 cd
SCP	3.34	3.58
Power Factor	1.0	
Emitted Color	Warm White	
Color Temp.	3000K	
CRI	75	
Viewing Angle	160°	
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x W0.63 inch / L36.58 x W016 mm	
Weight	0.02 lb / 0.3 oz / 8.5 g	



Ba15d Double-Contact Bayonet Base

LEDTRONICS®

America's Premium Brand LED Company™



23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424

E-mail: info@ledtronics.com
Website: ledtronics.com



To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDtronics.com