



Compact LED Bulbs, Low Voltage

14, 24 or 28 VAC/VDC – Ba15d Base – 130°~160° Beam Angle – 3000K or 4000K White



FEATURES

- 3 Year LEDtronics Warranty
- Direct Incandescent Replacement
- Low Power Consumption / Energy Savings up to 90%
- High Intensity / Even, Spherical Illumination
- Lumen Maintenance over 70% @ 15,000 Hours
- Compact Bulb Fits in Enclosed Fixtures & Tight Spaces
- Nickel Plated Brass / Dual-Contact Bayonet Base
- Wide Operating Temp. Range: -30°C to +50°C
- Solid-State: High-Shock & Vibration Resistant
- No UV, No RF Interference, Minimal Heat Generation

APPLICATIONS

- Suitable for Enclosed Fixtures Where Temperatures Do Not Commonly Exceed the Recommended Operating Range
- Indicator Lights for Instrumentation
- Panel-Mount Pilot Lights
- Accent Lighting

AVAILABLE OPTIONS

- Other White Color Temperatures
- Other Voltages

40 Years of LEDtronics Design, Engineering & Manufacturing Experience



3000K
Warm White

24
VAC/VDC



4000K
Natural White


Replaces Incandescent Bulbs
72, 624, 5626

Replaces GE 26567-624
Miniature Automotive Bulb

DB605SM-XIW-024V

Input Voltage	24VAC	24VDC
Input Power	1.3 Watts	1.2 Watts
Input Current	0.054A	0.050A
Efficacy (lm/W)	40	47
Total Lumens	51.7 lm	56.3 lm
Luminous Intensity	4.2 cd	7.1 cd
SCP	4.1	4.5
Power Factor	1.0	
Emitted Color	Warm White	
Color Temp.	3000K	
CRI	75	
Viewing Angle	140°	130°
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x W0.63 inch / L36.58 x W016 mm	
Weight	0.02 lb / 0.3 oz / 8.5 g	

5 LEDs



Ba15d Double-Contact
Bayonet Base

DB605SM-XNW-024V

Input Voltage	24VAC	24VDC
Input Power	1.2 Watts	1.1 Watts
Input Current	0.051A	0.048A
Efficacy (lm/W)	46	57
Total Lumens	52.92 lm	60.69 lm
Max. Candela	4.4 cd	7.9 cd
SCP	4.22	4.83
Power Factor	1.0	
Emitted Color	Natural White	
Color Temp.	4000K	
CRI	75	
Viewing Angle	160°	
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x W0.63 inch / L36.58 x W016 mm	
Weight	0.02 lb / 0.3 oz / 8.5 g	

LEDTRONICS®

America's Premium Brand LED Company™



© 2023 LEDtronics, Inc.

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505

Fax: (310) 534.1424

E-mail: info@ledtronics.com

Website: ledtronics.com



To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDtronics.com

LOG 823 / Rev 12-2023

Check LEDtronics.com for latest data.
Printed material may be outdated.




Replaces Incandescent
Bulbs 90, 68, 96, 1178

14 VAC/VDC

DB605SM-XIW-014V

Input Voltage	14VAC	14VDC
Input Power	1.6 Watts	1.3 Watts
Input Current	0.12A	0.09A
Total Lumens	88 lm	96 lm
Luminous Intensity	10 cd	11 cd
SCP	5.82	6.19
Emitted Color	Warm White	
Color Temp.	3000K	
CRI	75	
Viewing Angle	160°	
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x WØ0.63 inch / L36.58 x WØ16 mm	
Weight	0.01 lb / 0.16 oz / 4.53 g	



Ba15d Double-Contact
Bayonet Base

28 VAC/VDC

DB605SM-XIW-028V

Input Voltage	28VAC	28VDC
Input Power	1.1 Watts	1.0 Watts
Input Current	0.039A	0.037A
Efficacy (lm/W)	38.18	45
Total Lumens	42 lm	45 lm
Luminous Intensity	1.6 cd	4.8 cd
SCP	3.34	3.58
Power Factor	1.0	
Emitted Color	Warm White	
Color Temp.	3000K	
CRI	75	
Viewing Angle	160°	
Dimmability	Not Dimmable	
Operating Temp.	~-22°F to ~+122°F / ~-30°C to ~+50°C	
Base Type	Ba15d Double-Contact Bayonet	
Base Material	Nickel-Plated Brass	
Dimensions	L1.44 x WØ0.63 inch / L36.58 x WØ16 mm	
Weight	0.02 lb / 0.3 oz / 8.5 g	



Replaces Incandescent
Bulbs 304, 1252