



LED Area Flood Light with Adjustable Bracket

8 Watts – 100~277VAC – 4000K Natural White – Aluminum Housing – Clear Lens – IP65



FEATURES

- 5 Year LEDtronics Warranty
- Only 8 Watts – Energy Savings of up to 70% over HID Lamps
- Wide Input Voltage Range: 100~277VAC
- IP65 Rated – Water-Resistant for Outdoor Applications
- Long Life: Lumen Maintenance over 70% @ 100,000+ Hours
- Full Cutoff, 40°x45° Wide Beam Angle, Optimally Designed to Maximize Path Illumination
- Rugged, Industry-Standard Fixture: Die-Cast Aluminum
- Clear Tempered-Glass Lens
- Angular Adjustable U-Brackets – Multiple Mounting Options
- Improves Landscape Ambience & Security, Provides Accent Lighting While Reducing Energy Costs / Lightweight
- Solid State: High-Shock & High-Vibration Resistant
- Wide Ambient Operating Temperature Range: ~-22F to ~+113F [~-30C to ~+45C]

APPLICATIONS

Solar & Energy-Saving Applications Requiring Adjustable-Angle Uniform Illumination:

- Garden/Landscape Lighting
- Walkways/Pathways
- Amusement Parks/Recreation Areas
- Architectural Wall Washing
- Illuminate Signs & Pathways
- Emergency Exit Way Lighting

AVAILABLE OPTIONS

- Other LED CCTs: 5000K, 5700K, 6500
- Other Voltages
- Other Beam Angles

Over 35 Years of LEDtronics Design, Engineering w & Manufacturing Experience

GDL002-010W-XNW-101AM-B

Input Voltage	100~277VAC (Tested @ 120VAC)
Input Power	8 Watts
Input Current	0.11A
Max. Candela	1170 cd
Total Lumens	689 lm
Efficacy	88 lm/W
Power Factor	0.61
CRI	≥80
Illumination Angle	40° x 45°
Emitted Color	Natural White
Color Temperature	4000K
Dimmability	Not Dimmable
Oper. Temperature	-22°F ~+113°F -30°C ~+45°C
Housing	Aluminum (ADC12) / Black
Lens Material	Tempered Glass / Clear
Protection Rating	IP65
Dimensions (LxWxH) <i>(without Bracket)</i>	5.06 x 3.87 x 1.72 inch 128.5 x 98.3 x 43.6 mm
Weight	1.10 lbs / 0.5 kg



Glare-Free Design Enhances Night Vision



LEDTRONICS®

America's Premium Brand LED Company™



© 2022 LEDtronics, Inc.



23105 Kashiwa Court, Torrance, CA 90505
 Phone: (800) 579.4875 / (310) 534.1505
 Fax: (310) 534.1424
 E-mail: info@ledtronics.com
 Website: ledtronics.com

To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDtronics.com

WWW.LEDTRONICS.COM

LOG 872 / Rev 10 -2022

Check LEDTRONICS.COM for latest data. Printed material may be outdated.