



LED Linear Wall-Mount Light, 2 ft

24 Watts – 120~277VAC – Frosted White Lens – 110° Wide Beam – Dimmable – Wall or Ceiling Mounting



FEATURES

- 5 Year LEDtronics Limited Warranty
- Lumen Maintenance over 70% @ 50,000+ Hours
- Adjustable White Color Temperature: 3500K, 4000K & 5000K, with Both Uplight and Downlight Controlled Separately
- Features Microwave Sensor / Dimmable 0-10V
- Pendant Light with Both Direct & Indirect Lighting
- Can Be Mounted in Continuous, Seamless Runs to any Length
- Selectable Up, Down or Up-&-Down Illumination
- Lightweight, Durable Aluminum Housing
- Unique End Cap Simplifies Installation
- PS Frosted Diffuser Eliminates Glare
- Mounting Hardware for Wall, Ceiling or Suspended Mounting
- No Buzzing, No Flickering – Unlike Fluorescent Tubes
- No UV/IR Radiation, No RF Interference

APPLICATIONS

- Production Areas
- Canopies, Stairwells
- Offices, Lobbies, Showrooms
- Warehouse & Workshop Lighting
- Food Processing Facilities
- Equestrian Facilities / Farmyards
- Parking Areas & Garages
- Tunnels, Bridges

AVAILABLE OPTIONS

- 4 & 8 ft Lengths
- 120~347 Voltage
- Silver & Black Housing Finishes
- Sensor & Emergency Battery Backup

Over 40 Years of LEDtronics Design, Engineering & Manufacturing Experience

MOUNTING CHOICES

- Pendant
- Surface
- Wall
- Linkable

24 Watts

3 CCT
Tunable

INCLUDED HARDWARE

Color Temperature & Light
Distribution Field
Adjustable
Controls

LLA24-024W-3550K-101D-W-W-1

Nominal Power	3500K	4000K	5000K
Input Power	24 W	24W	24 W
Input Voltage	120~277VAC (Tested @ 120VAC)		
Total Lumens	3000 lm	3000 lm	3000 lm
Efficacy	125 lm/W	125 lm/W	125 lm/W
Power Factor	≥0.90		
CRI	80		
Beam Angle	110°		
Housing	Aluminum 6063-T5 / White		
Lens	PS / Frosted White		
Dimmability	Dimmable 0-10V		
LED	SMD2835		
Oper. Temp.	-20°C to +45°C / -4°F to +113°F		
Protection Rating	IP20		
Dimensions	L24 x W2.63 x H2.99 inch L609.6 x W66.8 x H75.95 mm		
Weight	4.1 lbs / 1.86 Kg		

TOP VIEW

2.63" [66.8mm]

BACK VIEW

2.99" [75.95mm]



LEDTRONICS®

America's Premium Brand LED Company™



23105 Kashiwa Court, Torrance, CA 90505

Phone: (800) 579.4875 / (310) 534.1505

Fax: (310) 534.1424

E-mail: info@ledtronics.com

Website: ledtronics.com



© 2024 LEDtronics, Inc.

To order LEDtronics products,
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

LEDtronics.com

www.LEDTRONICS.COM

LOG 897 / Rev 11-2024

Check LEDTRONICS.COM for latest data.
Printed material may be outdated.