



# Relampable LED Panel Indicators



## FEATURES

- 3 Year LEDtronics Warranty
- Energy Savings of up to 90%
- Solid State, High Shock Resistant
- Longer Life, Sustainability, Dependability
- RoHS Compliant

## APPLICATIONS

- Industrial Controls
- Panel Mount Retrofit Applications
- Visual Factory Controls
- Signaling Solutions
- Control Lighting
- Power Plant & Utilities Control Room
- Motor Control Panels

Over 35 Years of LEDtronics Design, Engineering & Manufacturing Experience

### Mounting Diameter 0.63" (16.0mm)

Series: RPLH16

Rear Mount / Front Relampable

Voltages: 48Vdc, 120 Vac/130Vdc, 250Vdc

Max Panel Thickness: 0.25" (6.35mm)

MOL: 2.13" (54.1mm)

Colors: Diffused White Waterclear Red Amber Yellow Green Blue

Replaces: ET16



### Mounting Diameter 0.87" (22.0mm)

Series: RPLH22

Rear Mount / Front Relampable

Voltages: 48Vdc, 120Vac/130Vdc

Max Panel Thickness: 0.25" (6.35mm)

MOL: 1.93" (49.0mm)

Colors: White Red Amber Yellow Green Blue

Replaces: 22mm Pilot Lights



### Mounting Diameter 1.19" (30.2mm)

Series: RPLH30

Rear Mount / Front Relampable

Voltages: 28 Vdc, 120Vac/130Vdc

Max Panel Thickness: 0.25" (6.35mm)

MOL: 2.27" (57.66mm)

Colors: White Red Amber Yellow Green Blue

Replaces: 30mm Pilot Lights



# LEDTRONICS

America's Premium Brand LED Company™



© 2021 LEDtronics, Inc.



23105 Kashiwa Court, Torrance, CA 90505  
Phone: (800) 579.4875 / (310) 534.1505  
Fax: (310) 534.1424  
E-mail: [info@ledtronics.com](mailto:info@ledtronics.com)  
Website: [ledtronics.com](http://ledtronics.com)

To order LEDtronics products,  
contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:

[LEDtronics.com](http://LEDtronics.com)

## Mounting Diameter .066" (16.0mm)

Series: PNL1145

Front Mount

**Voltages:** 24 Vdc - 60Vdc, 120Vac, 120Vac -130Vdc, 250Vdc

**Polarity:** Bipolar

**Max Panel Thickness:** 2.2" (56mm)

**MOL:** 3.25" (82.54mm)

**Colors:** Waterclear  Red  Amber  Green  Blue

**Replaces:** GE ET5 & GE ET6

**Optional:** Non-Relampable



---

## Mounting Diameter .069" (17.5mm)

Series: TSF780

Front Mount

**Voltages:** 24/28 Vdc, 120Vac

**Max Panel Thickness:** 0.25" (6.4mm)

**MOL:** 1.90/1.74" (48.26/44.20mm)

**Colors:** Red  Orange  Green

**Replaces:** 17.8mm Indicator Lights

**Optional:** Available with Dome Lens



## Mounting Diameter .069" (17.5mm)

Series: BSF780

Front Mount

**Voltages:** 24/28 Vdc, 120 Vac

**Max Panel Thickness:** 0.30" (7.62mm)

**MOL:** 2.11" (53.6mm)

**Colors:** Cool White  Red  Green

**Replaces:** 17.5mm Indicator Lights



## Mounting Diameter .069" (17.5mm)

Series: BSD780

Front Mount

**Voltages:** 24 Vdc/28 Vdc, 120Vac, 120Vdc, 130Vdc

**Max Panel Thickness:** 0.30" (7.62mm)

**MOL:** 2.11" (53.6mm)

**Colors:** Warm White  Cool White  Red  Orange  Yellow  Green

**Replaces:** 17.5mm Indicator Lights



## Mounting Diameter 0.375" (9.5mm)

Series: CSF370

Rear Mount

**Voltages:** 5 Vdc, 12/14Vdc, 24/28Vdc, 120Vac, 120Vdc, 130Vdc

**Max Panel Thickness:** X.XX" (X.XXmm)

**MOL:** 1.59" (40.5mm)

**Colors:** Cool White  Red  Orange  Yellow  Green  Blue

**Replaces:** Dialight Series 249-7xxx-33xx

**Optional:** Available with Dome or Low-Profile Lens



## Mounting Diameter 0.469" (11.7mm)

Series: MFS470

Front Mount

**Voltages:** 5 Vdc, 12/14Vdc, 24/28Vdc, 120Vac, 120Vdc, 130Vdc

**MOL:** 1.20" (30.5mm)

**Colors:** Cool White  Red  Yellow  Green

**Replaces:** 11.7mm Indicator Lights

**Optional:** Std Holder MIL# LH73/1 and LH89/1, Watertight, EMI/RFI Holder & Lens, Domed Lens



## Mounting Diameter 0.312" (8.0mm)

Series: HLC310

Front Mount

**Voltages:** 5 Vdc, 24/28 Vdc

**MOL:** 0.93" (23.6mm)

**Colors:** Red  Green

**Replaces:** 8.0mm Indicator Lights

**Optional:** Watertight Mounting Available



## Mounting Diameter 0.312" (8.0mm)

Series: HLD310

Rear Mount

**Voltages:** 5 Vdc, 24/28 Vdc

**MOL:** 0.93" (23.6mm) MOL

**Colors:** Warm White  Cool White  Red  Yellow  Green  Blue

**Replaces:** 8.0mm Indicator Lights

**Optional:** Watertight Mounting Available



*Since 1983, LEDtronics has created and manufactured over 10,000 different LED products, providing both customers and distributors with a wide variety of products to successfully meet their lighting needs.*

*Our LED Lighting products of today continue fulfilling our mission statement that began in 1983:*

- Provide energy-efficient and environmentally friendly LED lighting products to our customers
- Use our innovative skills to address specific needs of our customers
- Offer the correct and most beneficial solutions for our customers
- Provide expert technical assistance to our customers