Relampable LED Panel Indicators

FEATURES

- 3 Year LEDtronics Warranty
- Energy Savings of up to 90%
- Solid State, High Shock Resistant
- Longer Life, Sustainability, Dependability
- RoHS Compliant

APPLICATIONS

- Industrial Controls
- Panel Mount Retrofit Applications
- Visual Factory Controls
- Signaling Solutions
- Control Lighting
- Power Plant & Utilities Control Room
- Motor Control Panels

More than 40 Years of LEDtronics Design, Engineering & Manufacturing Experience

Mounting Diameter 0.63" (16.0mm)
Series: RPLH16

Rear Mount / Front Relamapable

Voltages: 48VDC, 120VAC/130VDC, 250VDC
Max Panel Thickness: 0.25" (6.35mm)
MOL: 2.13" (54.1mm)
Colors: Diffused White ○ Waterclear ○ Red ● Amber ● Yellow ● Green ● Blue ●
Replaces: ET16

RoHS COMPLIANT

Mounting Diameter 0.63" (16.0mm)
Series: RPLH16-0ER/0CW

Rear Mount / Front Relamapable

Voltages: 110/140VDC, 220/280VDC
Max Panel Thickness: 0.25" (6.35mm)
MOL: 2.50" (63.5mm)
Colors: Cool White ○ Super Red & White ● AquaGreen & White ●

Mounting Diameter 0.63" (16.0mm)
Series: RPLH16-02Z47

Rear Mount / Relamapable / Fluted Lens

Voltages: 130VDC/120VAC, 50VDC Turn-On
Max Panel Thickness: 0.25" (6.35mm)
Colors: White ○ Red ● Amber ● Yellow ● Green ● Blue ●
Comparable to: UL 508 & NEMA 3, 4, 4X, 5, 6, 12

LEDTRONICS®
America's Premium Brand LED Company™

ISO 9001:2015 CERTIFIED by DNV

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424
E-mail: info@ledtronics.com
Website: ledtronics.com

© 2025 LEDtronics, Inc.

To order LEDtronics products, contact the Distributor or Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our worldwide network:
LEDtronics.com

LOG 443 / Rev 12-2025

Check LEDTRONICS.COM for latest data. Printed material may be outdated

Relampable Panel Indicators

Direct Incandescent Replacements
Up to 90% Energy Savings – Long Life – No Heat

Mounting Diameter 0.87" (22.0mm)
Series: RPLH22

Rear Mount / Front Relamapable

Voltages: 48VDC, 120VAC/130VDC
Max Panel Thickness: 0.25" (6.35mm)
MOL: 1.93" (49.0mm)
Colors: White ○ Red ● Amber ● Yellow ● Green ● Blue ●

Replaces: 22mm Pilot Lights

RoHS COMPLIANT

Mounting Diameter 1.19" (30.2mm)
Series: RPLH30

Rear Mount / Front Relamapable

Voltages: 28 VDC, 120VAC/130VDC
Max Panel Thickness: 0.25" (6.35mm)
MOL: 2.27" (57.66mm)
Colors: White ○ Red ● Amber ● Yellow ● Green ● Blue ●

Replaces: 30mm Pilot Lights

RoHS COMPLIANT

Mounting Diameter .066" (16.0mm)
Series: PNL1145

Front Mount

Voltages: 24 VDC - 60VDC, 120VAC, 120VAC -130VDC, 250VDC
Polarity: Bipolar
Max Panel Thickness: 2.2" (56mm)
MOL: 3.25" (82.54mm)
Colors: Waterclear ○ Red ● Amber ● Green ● Blue ●

Replaces: **GE ET5 & GE ET6**

Optional: Non-Relampable

RoHS COMPLIANT

Mounting Diameter .069" (17.5mm)
Series: TSF780

Front Mount

Voltages: 24/28 VDC, 120VAC
Max Panel Thickness: 0.25" (6.4mm)
MOL: 1.90/1.74" (48.26/44.20mm)
Colors: Red ● Orange ● Green ●

Replaces: 17.8mm Indicator Lights

Optional: Available with Dome Lens

RoHS COMPLIANT

E-mail: info@ledtronics.com
Website: ledtronics.com

LEDTRONICS®
America's Premium Brand LED Company™

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424

Relampable Panel Indicators

Direct Incandescent Replacements
Up to 90% Energy Savings – Long Life – No Heat

Mounting Diameter 0.69" (17.5mm)
Series: BSF780

Front Mount

Voltages: 24/28 VDC, 120 VAC
Max. Panel Thickness: 0.30" (7.62mm)
MOL: 2.11" (53.6mm)
Colors: Cool White ○ Red ● Green ● Orange ●

Replaces: 17.5mm Indicator Lights

RoHS COMPLIANT

Mounting Diameter 0.69" (17.5mm)
Series: TSD780

Front Mount, Dome Fluted Lens, T2-#5 Slide Base

Voltages: 12/14VDC, 24/28VDC, 120VAC
Max. Panel Thickness: 0.25" (6.35mm)
MOL: 2.11" (53.6mm)
Colors: Warm White ○ Red ● Orange ● Yellow ● Green ●

Replaces: 17.5mm Indicator Lights

Mounting Diameter .69" (17.5mm)
Series: BSD780

Front Mount

Voltages: 24 VDC/28 VDC, 120VAC, 120VDC, 130VDC
Max. Panel Thickness: 0.30" (7.62mm)
MOL: 2.11" (53.6mm)

Colors: Warm White ○ Cool White ○ Red ● Orange ● Yellow ● Green ●

Replaces: 17.5mm Indicator Lights

RoHS COMPLIANT

Mounting Diameter 0.375" (9.5mm)
Series: CSF370

Rear Mount

Voltages: 5 VDC, 12/14VDC, 24/28VDC, 120VAC, 120VDC, 130VDC
Max. Panel Thickness: X.XX" (X.XXmm)
MOL: 1.59" (40.5mm)

Colors: Cool White ○ Red ● Orange ● Yellow ● Green ● Blue ●

Replaces: Dialight Series 249-7xxx-33xx

Optional: Available with Dome or Low-Profile Lens

RoHS COMPLIANT

E-mail: info@ledtronics.com
Website: ledtronics.com

LEDTRONICS®
America's Premium Brand LED Company™

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424

Relampable Panel Indicators

Direct Incandescent Replacements
Up to 90% Energy Savings – Long Life – No Heat

Mounting Diameter 0.469" (11.7mm)
Series: MFS470

Front Mount

Voltages: 5 VDC, 12/14VDC, 24/28VDC, 120VAC, 120VDC, 130VDC

MOL: 1.20" (30.5mm)

Colors: Cool White ○ Red ● Yellow ● Green ●

Replaces: **11.7mm Indicator Lights**

Optional: Std Holder MIL# LH73/1 and LH89/1, Watertight, EMI/RFI Holder & Lens, Domed Lens

RoHS COMPLIANT

Mounting Diameter 0.312" (8.0mm)
Series: HLC310

Front Mount

Voltages: 5 VDC, 24/28 VDC

MOL: 0.93" (23.6mm)

Colors: Red ● Green ●

Replaces: 8.0mm Indicator Lights

Optional: Watertight Mounting Available

Mounting Diameter 0.312" (8.0mm)
Series: HLD310

Rear Mount

Voltages: 5 VDC, 24/28 VDC

MOL: 0 .93" (23.6mm) MOL

Colors: Warm White ○ Cool White ○ Red ● Yellow ● Green ● Blue ●

Replaces: 8.0mm Indicator Lights

Optional: Watertight Mounting Available

Since 1983, LEDtronics has created and manufactured over 10,000 different LED products, providing both customers and distributors with a wide variety of products to successfully meet their lighting needs.

Our LED Lighting products of today continue fulfilling our mission statement that began in 1983:

- Provide energy-efficient and environmentally friendly LED lighting products to our customers
- Use our innovative skills to address specific needs of our customers
- Offer the correct and most beneficial solutions for our customers
- Provide expert technical assistance to our customers

LEDTRONICS®
America's Premium Brand LED Company™

© 2023 LEDtronics, Inc.

scmbdc® Southern California Minority Business Development Council

23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579.4875 / (310) 534.1505
Fax: (310) 534.1424
E-mail: info@ledtronics.com
Website: ledtronics.com